





Customer Display



Extraordinary Power. Exceptional Value.

With premium-class presets, fast print speed, and more labeling functions, you are getting more flexibility and more features – all for less cost than comparable price computing scales with printers.

Three Configurations

With three models and two display types, you can easily find a Uni-3 to fit your specific application needs.

Two Communication Choices

Ethernet or optional wireless communication enables any Uni-3 to be added to your existing network - ensuring you have consistent control of all scales in your store.



ScaleLink Pro 5 Lite

Product management software ensures easy file maintenance as well as PLU and tare weight consistency throughout your operation.

Flexible Presets

The power of the Uni-3 is at your fingertips with flexible preset buttons to represent PLUs, container tare values, label formats, images, and logos.

Two Display Types

The Uni-3 L1 model features a vibrant blue alphanumeric display with a sharp white 16-segment capability. The Uni-3 L2 model features a clear alphanumeric LCD display with one line alphanumeric and one line numeric only. Each model offers a matching customer display.



Uni-3L2

Standard Features

- Dual-range weighing (0-15lb x 0.005lb/15-30lb x 0.01lb)
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Up to 168 function keys assist with intuitive operation
- Fast printing speed
- Meat nutrition labeling
- Multiple label formats for multi-department support
- Powerful batch printing feature
- Flash ROM for remote update of application software
- Proportional tare
- Side-load labels
- Compatible with third-party communication software, including ADC's InterScale and Invatron's PLUM





Options/Accessories

- Wireless communication, 802.11 b/g
- SLP-5 and SLP-5 Lite scale management software, including label design, data backup and remote diagnostics
- Produce platter
- Fish platter

Specifications

Capacity:

Display items:

Dual-range: 15 lb x 0.005 lb/15-30 lb x 0.01 lb Weighing resolution: Display types:

3,000 display divisions maximum

LCD, blue, alphanumeric: L1 (23 digits 16 seg) LCD, backlit, alphanumeric: L2 (192 × 16 dot

matrix + 23 digits 7 seg) Tare: four digits

Unit price: five digits Total price: six digits

Pole model: 84 one-touch preset keys 168 presets (assign two items/key) Preset keys:

Hanging model: 94 one-touch preset keys 188

presets (assign two tare/key)

Countertop models: 14.5 in x 10.5 in Platter:

Hanging model: 14.1 in diameter

Memory capacity:

TCP/IP 10/100 Base T Ethernet Communication: Printing speed: 3.9 in (100 mm) per second Label: Width: 1.5in-2.5in (38mm-64mm) Length: 1.2 in-6.9 in (30 mm-175 mm) Label roll:

Inside diameter: 1.6 in (40 mm) Outside diameter: 3.9 in (100 mm) Width: up to 2.6 in (66 mm)

Label backing paper: AC 100V/120V/220V/240V, 50/60 Hz Power supply: Stand-by: 50W. In operation: 100W Power consumption:

Classification: NTEP CC 07-005 Warranty: One-year limited warranty Printing: Direct thermal

Thermal head: 2.2 in (56 mm) (448 dot, 8 dot/mm)

Approvals











Your Rice Lake Weighing Systems distributor is:

Interweigh Systems Inc. Phone: 800-268-3269

e-mail: inquiry@interweigh.ca www.InterweighSystems.ca



