



Expand Your Range of Applications
with the IG Series of Digital Platform Scales

IGB

IG
SERIES

IG SERIES

Simple to Use Tare Function

Place a container on the platform and press the Tare key.

The tare is automatically stored in memory and the net weight is displayed during each subsequent weighing.

Easy-to-Read, Rotating Display

Choose a large bright VFD display or a vivid LCD display to meet your application needs and ease operator reliability.

For optimum viewing, and to help eliminate errors, the indicator head can be vertically adjusted with the turn knobs.

Check Weighing Function Simplifies Control

When the user defined upper limit is exceeded, the letter "H" is displayed.



When the value is under the lower limit, "L" is displayed. An audible beep warns the operator that the item is out of tolerance.

Auto Power Off Function


The IGB model features battery operation with a selectable automatic power-off function (10, 20, 30, 40, 50, 60 minutes or off) to extend battery life.

For those applications where AC power is available select either the IGB with optional AC adaptor or IGX.

Specifications (IGX & IGB)

Model	 IGX	 IGB
Capacity (Minimum graduation)	150 kg (50 g) 60 kg (20 g) ----- 150 kg / 300 lb (0.05 kg / 0.1 lb) <USA, Canada only> 60 kg / 150 lb (0.02 kg / 0.05 lb)	
Accuracy	Selectable 1 / 3000, 1 / 6000, 1 / 7500, NOTE: Legal for Trade setting is 1 / 3000	
Weight indicator	5 digit, 29 mm (1.14") VFD	5 digit, 25 mm (0.98") LCD
Display annunciators	ZERO (▼) TARE (▼)	
Weight	16.8 kg / 37.04 lb	16.0 kg / 35.23 lb
Operating temperature	-5 °C to 40 °C (23 °F to 109 °F)	
Electrical power	AC100 V, 120 V, 220 V, 240 V	(2) D size batteries or AC Adaptor Note: Up to 500 hours of continuous use with alkaline, dry batteries

Dimensions unit: mm (inch)



 **ISHIDA**

 **ISHIDA CO., LTD.**

Distributed by:
Interweigh Systems Inc.
PHONE : 800-268-3269
email: inquiry@interweigh.ca
URL: www.InterweighSystems.ca

Specifications subject to change without notice